

Power Inductor – RA7338-AE

For Microchip 1600W Bus
Balancer Reference Design



- High current, high inductance power inductors
- Designed for high current power supply applications
- Flat wire windings provide extremely low DC and AC resistance.
- Suitable for high temperature environments, up to 125°C ambient
- AEC-Q200 Grade 1 (–40°C to +125°C)
- Shield has solderable tabs for additional mounting stability.

Core material Ferrite

Environmental RoHS compliant, halogen free

Terminations RoHS compliant tin-silver over copper

Shield tabs RoHS compliant bright tin over nickel over stainless steel

Weight 109 g

Ambient temperature –40°C to +125°C with Irms current,

Maximum part temperature +165°C (ambient + temp rise).

Storage temperature Component: –40°C to +165°C.

Tray packaging: –40°C to +80°C

Moisture Sensitivity Level (MSL) 1 (unlimited floor life at <30°C / 85% relative humidity)

Packaging 9 parts per tray

PCB washing Tested to MIL-STD-202 Method 215 plus an additional aqueous wash. See [Doc787 PCB Washing.pdf](#).

Part number	Inductance (μH) ¹		DCR (mOhms) ²		SRF (MHz)	Isat (A) ³			Irms (A) ⁴	
	min	max	typ	max		10% drop	20% drop	30% drop	20°C rise	40°C rise
RA7338-AE	17.6	24.2	0.68	0.75	9.25	19	22	24	34.0	44.5

1. Inductance tested at 100 kHz, 0.1 Vrms on Agilent/HP 4192A.

2. DCR measured on a Keithley 580 micro-ohmmeter or equivalent.

3. DC current at 25°C that causes an inductance drop of 30% (typ) from its value without current. [Click for temperature derating information.](#)

4. Current that causes the specified temperature rise from 25°C ambient. This information is for reference only and does not represent absolute maximum ratings. [Click for temperature derating information.](#)

5. Electrical specifications at 25°C.

Refer to Doc 362 “Soldering Surface Mount Components” before soldering.



www.coilcraft.com

US +1-847-639-6400 sales@coilcraft.com

UK +44-1236-730595 sales@coilcraft-europe.com

Taiwan +886-2-2264 3646 sales@coilcraft.com.tw

China +86-21-6218 8074 sales@coilcraft.com.cn

Singapore + 65-6484 8412 sales@coilcraft.com.sg

Document 1300-1 Revised 03/15/22


© Coilcraft Inc. 2022

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.







Power Inductor - RA7338-AE

Typical L vs Current



Typical L vs Frequency



Dimensions are in inches / mm



US +1-847-639-6400 sales@coilcraft.com
UK +44-1236-730595 sales@coilcraft-europe.com
Taiwan +886-2-2264 3646 sales@coilcraft.com.tw
China +86-21-6218 8074 sales@coilcraft.com.cn
Singapore + 65-6484 8412 sales@coilcraft.com.sg

Document 1300-2 Revised 03/15/22

© Coilcraft Inc. 2022

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.